

# Performance Data Sheet

Model: AP717

Chemical Reduction Filter

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42.



System tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of substances listed below.

Capacity 1,500 Gallons (5,678 Liters) Contaminant Reduction Determined by NSF testing.

Contaminant Reduction	Average Influent	NSF/ANSI Specified Challenge Concentration	Avg % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.0 mg/L	2.0 mg/L ± 10%	67.0%	0.66 mg/L	N/A	≥ 50%	515984-04

Application Guidelines/Water Supply Parameters	
Service Flow	0.5 gpm (1.89 lpm)
Water Supply	Potable Water
Water Pressure	25 -125 psi (172 – 862 kPa)
Water Temperature	33° F - 100° F (0.6° C - 38° C)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

**Note:** While the testing was performed under standard laboratory conditions, actual performance may vary.

Replacement Cartridge: AP717. For estimated costs of replacement elements please call 1-800-222-7880 or visit our website at [www.cuno.com](http://www.cuno.com)

**WARNING**

**To reduce the risk associated with ingestion of contaminants:  
Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system.**

**CAUTION**

**To reduce the risk associated with property damage due to water leakage:**

- **Read and follow** Use Instructions before installation and use of this system.
- Installation and use **MUST** comply with all state and local plumbing codes.
- **Do not** install if water pressure exceeds 125 psi (862 kPa). If your water pressure exceeds 80 psi, you **must** install a pressure limiting valve. Contact a plumbing professional if you are uncertain how to check your water pressure.
- **Do not** install where water hammer conditions may occur. If water hammer conditions exist you **must** install a water hammer arrester. Contact a plumbing professional if you uncertain how to check for this condition.
- **Do not** install on hot water supply lines. The maximum operating water temperature of this filter system is 100° F (38° C).
- **Protect filter from freezing.** Drain filter when temperatures drop below 33°F (0.6°C). The disposable filter cartridge **must** be replaced every 6 months, at the rated capacity or if a noticeable reduction in flow rate occurs.

CUNO is a trademark of 3M Company used under license.  
 3M is a trademark of 3M Company.  
 NSF is a trademark of NSF International.  
 © 2008 3M Company. All rights reserved.  
 INSTR2056 0409

Parts and service available from:



CUNO Incorporated  
 400 Research Parkway  
 Meriden, CT 06450 U.S.A  
 Toll Free: 1-800-222-7880  
 Worldwide: 203-237-5541  
[www.aquapure.com](http://www.aquapure.com) • [www.cuno.com](http://www.cuno.com)