

CONTROLLERS



SIMPLICITY

LXT

- ▶ Midsize LCD display (5800 only)
- ▶ Pre-programmed
- ▶ Applicable to filter or softener systems



COMPLETELY CUSTOMIZABLE

SXT

- ▶ Large LCD display
- ▶ One programmable relay output
- ▶ Applicable to filter or softener systems



CONTROLLER ENHANCED

XTR2

- ▶ Premium touch screen LCD display
- ▶ Customizable programming
- ▶ Field programmable



5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
P: 262.238.4400 | F: 262.238.4404
WATERPURIFICATION.PENTAIR.COM
CUSTOMER CARE: 800.279.9404 | tech-support@pentair.com
© 2017 Pentair Residential Filtration, LLC. All rights reserved.

For a detailed list of where Pentair trademarks are registered, please visit waterpurification.pentair.com/brands. Pentair trademarks and logos are owned by Pentair plc or its affiliates. Third party registered and unregistered trademarks and logos are the property of their respective owners.
4004315 Rev E JL17



FLECK 5800 SERIES VALVES

CONTINUING THE LEGACY



MADE IN THE
USA
OF FOREIGN & DOMESTIC PARTS

PRODUCT OVERVIEW

The 5800 Series of Pentair Fleck® valves provide a common solution for a wide variety of filtration and softening applications. Developed on the same platform as the 5800, the 5810 and 5812 valves offer flexibility with a familiar appearance, while reducing carrying costs.

The 5800 Series provides:

- ▶ **HIGH-FLOW SOLUTIONS** for large residential and small commercial applications
- ▶ **FAMILIAR** - Uses the same Pentair powerhead and controller options
- ▶ **STANDARD VALVE BODY** for upflow, downflow and filter applications
- ▶ **EASILY SERVICED** with the same snap fit and seal and spacer principles



MAX
FLOW RATES
(GPM)

5800

5810

5812

SERVICE	5800	5810	5812
PEAK	21	36	43
BACKWASH	27	47	56
DOWNFLOW	17	28	33

Downflow valve only

FEATURES

5812
High Performance flexible 1-1/4" Valve

- Filter Plastic Piston
- Upflow Plastic Piston
- Downflow Plastic Piston
- Mechanical Stops
To prevent overtightening of plastic nuts
- Seal & Spacer "snap-together" Cartridge with EPDM (black) Seals
For extended service life and simplified replacement
- 2.5" & 4" threaded base
- End Cap/Plug
Easily installed or removed using a screwdriver or hex wrench
- Side Mount Meter
With encapsulated magnets for reduced maintenance

5810
High Performance flexible 1" Valve