## **HARMSCO®**

# **Calypso Blue™ Cartridges**

Industrial and Residential

## **Premium and WaterBetter Series**

Designed for 4-1/2" diameter filter housings.

Highly efficient filter cartridges available in a selection of media including the industry's largest surface area.



Lower overall operating cost Longer filter runs for fewer change outs Lower initial pressure drops Reduced maintenance down time and cost Increased contaminant removal High flow capability

#### **Features**

- Pleated design for more surface area
- FDA approved materials NSF 61 certified
- Engineered media for superior performance
- Cleanable and reusable in most applications and micron sizes
- Thermally bonded end caps to ensure better sealing
- Full product line largest selection of micron ratings
- Optional High Temperature cartridges available



## **Applications**

- Reverse Osmosis Pre-filtration
- Municipal Drinking Water Filtration
- Commercial/Residential Drinking Water Filtration
- Desalination Pre-filtration
- Industrial Water Filtration

- Cooling Tower Filtration
- Chill Water Loop Filtration
- Food & Beverage Filtration
- Marine/Aquatic Filtration





### **Specifications**

- Nominal Micron Ratings: 0.35, 1, 5, 20, 50 microns Absolute Micron Rating: 1 micron
- Filter Media: Polyester Plus, Synthetic, Nano Fiber
- End Caps: Pliable PVC with sealing surface built in
- Shrink Wrap: Standard on all Premium and WaterBetter Calypso cartridges
- Temperature: up to 140°F (60°C)
- Center Tubes: ABS or PVC



### **Cartridge Selection/Sizing Guide**

9-3/4"

20"

Certified to ANSI-NSF 61 **Excluding High Temp Cartridges** 

Product Code	Nominal	Media	Maximum	Length	0.D.	No./Case
	Micron Rating	(sq ft)	Flow Rate* (GPM)	(in)	(in)	3.,7.2.30
Polyester - engir	neered for high efficiency, low	pressure drops				
HB-10-0.35W	0.35	12	12	9-3/4	4-1/2	8
HB-10-1W	1	12	12	9-3/4	4-1/2	8
HB-10-5W	5	12	12	9-3/4	4-1/2	8
HB-10-20W	20	12	12	9-3/4	4-1/2	8
HB-10-50W	50	12	12	9-3/4	4-1/2	8
HB-20-0.35W	0.35	26	26	20	4-1/2	4
HB-20-1W	1	26	26	20	4-1/2	4
HB-20-5W	5	26	26	20	4-1/2	4
HB-20-20W	20	26	26	20	4-1/2	4
HB-20-50W	50	26	26	20	4-1/2	4
<b>Harmsco Free</b>	- 100% synthetic composite	media				
HB-10-1W-HF	1	8	8	9-3/4	4-1/2	8
HB-10-5W-HF	5	8	8	9-3/4	4-1/2	8
HB-10-20W-HF	20	8	8	9-3/4	4-1/2	8
HB-20-1W-HF	1	20	20	20	4-1/2	4
HB-20-5W-HF	5	20	20	20	4-1/2	4
HB-20-20W-HF	20	20	20	20	4-1/2	4
Poly-Pleat - 1 m	icron absolute, multi-layed m	edia				
PP-BB-10-1	1	8	4	9-3/4	4-1/2	8
PPFS-BB-10-1	1	8	4	9-3/4	4-1/2	8
PP-BB-20-1	1	20	10	20	4-1/2	4
PPFS-BB-20-1	1	20	10	20	4-1/2	4
SureSafe Antir	microbial - reduces grov	wth of bacteria and	mold on media			
HB-10-20W-AM	20	12	12	9-3/4	4-1/2	8
HB-10-50W-AM	50	12	12	9-3/4	4-1/2	8
HB-20-20W-AM	20	26	26	20	4-1/2	4
HB-20-50W-AM	50	26	26	20	4-1/2	4
EZ-Clean - 100%	synthetic composite 50 micr	on media				
HB-10-EZ-CLEAN	30	12	12	9-3/4	4-1/2	8
HB-20-EZ-CLEAN	30	26	26	20	4-1/2	4
Water Batter B	alvantau					
	<b>olyester -</b> economy grad		10	0.2/4	4.1/0	0
WB-HB-10-1W WB-HB-10-5W	<u> </u>	9.5 9.5	10 10	9-3/4 9-3/4	4-1/2 4-1/2	8
	5 20	9.5	10	9-3/4		8
WB-HB-10-20W					4-1/2	
WB-HB-10-50W	50	9.5	10	9-3/4	4-1/2	8
WB-HB-20-1W	1	21	20	20	4-1/2	4
WB-HB-20-5W	5	21	20	20	4-1/2	4

<sup>\*</sup> Harmsco recommends operation at 50-70% of maximum flow rate for optimum performance.

20

50



WB-HB-20-20W

WB-HB-20-50W

**HARMSCO®** Filtration Products

21

www.harmsco.com

4-1/2

4-1/2

20

20



20