

STRUCTURAL[®]

RETENTION VESSELS



FEATURES/BENEFITS

Quick connect design

Threadless connection eliminates potential for cross threading or over torquing

Multiple plumbing connections available: brass or plastic, NPT, BSP, glued socket or sweat

Vessel of choice for chemical treatment

Provides optimal contact time

Seamless inner shell of molded

polyethylene for impact and corrosion resistance

Miles of epoxy covered fiberglass filament for superior strength and lightweight

Inlet/outlet PVC pipe connections offer application flexibility

Adaptable for both new and replacement installation

Additional drain port

SPECIFICATIONS

MODEL #	PART #	TOP CONNECTION	BOTTOM CONNECTION	DIMENSIONS	CAPACITY
CT-30	31534-1	1-1/4" socket Q.C.	1-1/4" male	16 x 44.5" (41 x 113 cm)	30 gal (113.5 L)
CT-40SQ	31533-1	1-1/4" socket Q.C.	1-1/4" male	21 x 36" (53 x 91 cm)	40 gal (151.2 L)
CT-40	31608-1	1-1/4" socket Q.C.	1-1/4" male	16 x 57.25" (40.6 x 145 cm)	40 gal (151.2 L)
CT-80	30957-1	1-1/4" socket Q.C.	1-1/4" male	21 x 62.75" (53 x 159 cm)	80 gal (302.4 L)
CT-120	31057-1	1-1/4" socket Q.C.	1-1/4" male	24 x 73.25" (61 x 186 cm)	120 gal (454 L)



FILTRATION & PROCESS

5730 NORTH GLEN PARK ROAD, MILWAUKEE, WI 53209
262.238.4400, CUSTOMER CARE: 800.279.9404, WWW.PENTAIRAQUA.COM

All Pentair trademarks and logos are owned by Pentair, Inc. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

40847 Rev B MR14 © 2014 Pentair Residential Filtration, LLC. All Rights Reserved.